



COMPLEMENTARY MATERIALS

[CLICK HERE](#)



PACIFICA RIFT OAK

PACIFICA RIFT OAK IS A WARM CREAMY CLASSIC NEUTRAL, WITH RICH CHOCOLATE HIGHLIGHTS OFFERING THE OPPORTUNITY FOR UNEXPECTED CONTRASTS AND MAGICAL MOMENTS. IT IS A CLEAN CRISP WOODGRAIN DESIGN THAT IS ACCENTED BY THE LATEST MODERN TEXTURE, CONTRIBUTING TO ITS APPEALING HAPTIC QUALITY AND CREATING A MODERN SUBTLE NEUTRAL. PACIFICA RIFT OAK DELIVERS THE PERFECT BALANCE OF ORGANIC STRENGTH AND MODERN SERENITY. IDEAL FOR VERTICAL AND HORIZONTAL APPLICATIONS, IT TRANSFORMS KITCHENS, CABINETRY, WALLS, FURNITURE, AND COMMERCIAL SPACES WITH GROUNDED ELEGANCE AND ENDURING PRESENCE. PACIFICA RIFT OAK IS OFFERED IN A FURNITURE LIKE TEXTURED FINISH AND IS SUITABLE FOR VERTICAL AND HORIZONTAL APPLICATIONS. IT IS EASY TO CLEAN, DOESN'T CHIP, IS HIGHLY DURABLE AND HAS LONG TERM UV STABILITY.

PRODECOR® 2D PP FILM
COLOR CODE: SSSI/011
PARALLEL ✓





PACIFIC RIFT OAK

PRODECOR® 2D PP FILM

STOCK RANGE ✓ PARALLEL ✓

COLOR CODE: SSI/011 EMBOSSING: MODERN WOODPORE

PERFORMANCE SUMMARY

- BLEACH SOLUTION CLEANABLE
- EXCELLENT SOIL & STAIN RESISTANCE
- NATURAL FLUID BARRIER
- EXCELLENT ABRASION & IMPACT RESISTANCE
- EXCELLENT COLOR STABILITY

ENVIRONMENTAL

- NO ADDED FLAME RETARDANTS
- NO ADDED ANTIMICROBIALS
- DOES NOT CONTAIN FORMALDEHYDE
- FORMULATED WITHOUT PHTHALATES

CLEANING AND MAINTENANCE

• WATER AND MILD LIQUID SOAP CLEANABLE

ITEM SPECIFICATIONS

BRAND NAME: PRODECOR

CONTENT: POLYPROPYLENE

MOQ: NONE

SURFACE TEXTURE / EMBOSSING: MODERN WOODPORE

SURFACE GLOSS: 3

SURFACE FINISH LACQUER:

SCRATCH & STAIN RESISTANT EXCIMER TOPCOAT

GAUGE: 150MY (.006") WIDTH: 1,300MM (51.18")

ROLL SIZE: 500LM

DESIGN REPEAT (RAPPORT): 1260MM (49.6")

SUITABLE FOR: FLAT LAMINATION, PROFILE WRAPPING

PERFORMANCE CHARACTERISTICS

TESTING DONE IN ACCORDANCE TO: ISO 4586-1 2018-07
150MY SOLID AND 150MY PRINTED EXCIMER TOP COATED
PRODECOR TESTED

#11 RESISTANCE TO SURFACE WEAR

SOLIDS (150MY): 1550

PRINTS (150MY): 150

#25 RESISTANCE TO IMPACT BY LARGE DIAMETER BALL:

1600MM (62.99")

#29 RESISTANCE TO SCRATCHING: RATING 3

#31 RESISTANCE TO STAINING (METHOD B)

CLEANABILITY SCORE: 16

*MUSTARD SEVERE EFFECT *IODINE MODERATE EFFECT

#33 LIGHT FASTNESS (XENON ARC) (METHOD B)

(5) NO EFFECT (SOLID OR PRINT)

#41 RESISTANCE TO WET HEAT (100° C)

(5) NO VISABLE CHANGE

ASTM E84: CLASS A

REDUCED ENVIRONMENTAL IMPACT

R.E.A.C.H. COMPLIANT

MANUFACTURED WITHOUT PLASTICIZERS OR HEAVY

METALS FIRE CLASSIFICATION EN 13501-1 - CFI - S1



COMPLEMENTARY MATERIALS

[CLICK HERE](#)

