



COMPLEMENTARY MATERIALS

[CLICK HERE](#)



TIMBERLINE RUSTIC OAK

TIMBERLINE RUSTIC OAK REFLECTS THE RUGGED BEAUTY FORGED BY THE PACIFIC NORTHWEST. SUBTLE WEATHERED GRAYS AND MINERAL STREAKS INTERTWINE WITH WARM HONEYED AMBERS AND RICH TAUPE UNDERTONES, EVOKING STORMY SKIES, ROCKY SHORES, AND TIMELESS COASTAL TIMBER. THE PRONOUNCED TACTILE TEXTURE ADDS AUTHENTIC DEPTH AND DIMENSION, DELIVERING BOTH VISUAL DRAMA AND A SATISFYING HAND-FEEL THAT BRINGS THE OUTDOORS IN. THIS BOLD WOODGRAIN DESIGN CAPTURES A DRAMATIC HAND-HEWN CHARACTER WITH DEEP, GRAIN MOVEMENT THAT FLOWS LIKE SHIFTING EARTH AND DRIFTING MIST.

TIMBERLINE RUSTIC OAK IS OFFERED IN A FURNITURE LIKE TEXTURED FINISH AND IS SUITABLE FOR VERTICAL AND HORIZONTAL APPLICATIONS. IT IS EASY TO CLEAN, DOESN'T CHIP, IS HIGHLY DURABLE AND HAS LONG TERM UV STABILITY.

PRODECOR® 2D PP FILM
COLOR CODE: SSI/031
PARALLEL ✓





TIMBERLINE RUSTIC OAK

PRODECOR® 2D PP FILM

STOCK RANGE ✓ PARALLEL ✓

COLOR CODE: SSI/031. EMBOSSING: MODERN WOODPORE

PERFORMANCE SUMMARY

- BLEACH SOLUTION CLEANABLE
- EXCELLENT SOIL & STAIN RESISTANCE
- NATURAL FLUID BARRIER
- EXCELLENT ABRASION & IMPACT RESISTANCE
- EXCELLENT COLOR STABILITY

ENVIRONMENTAL

- NO ADDED FLAME RETARDANTS
- NO ADDED ANTIMICROBIALS
- DOES NOT CONTAIN FORMALDEHYDE
- FORMULATED WITHOUT PHTHALATES

CLEANING AND MAINTENANCE

• WATER AND MILD LIQUID SOAP CLEANABLE

ITEM SPECIFICATIONS

BRAND NAME: PRODECOR

CONTENT: POLYPROPYLENE

MOQ: NONE

SURFACE TEXTURE / EMBOSSING: MODERN WOODPORE

SURFACE GLOSS: 3

SURFACE FINISH LACQUER:

SCRATCH & STAIN RESISTANT EXCIMER TOPCOAT

GAUGE: 150MY (".006") WIDTH: 1,300MM (51.18")

ROLL SIZE: 500LM

DESIGN REPEAT (RAPPORT): 1260MM (49.6")

SUITABLE FOR: FLAT LAMINATION, PROFILE WRAPPING

PERFORMANCE CHARACTERISTICS

TESTING DONE IN ACCORDANCE TO: ISO 4586-1 2018-07
150MY SOLID AND 150MY PRINTED EXCIMER TOP COATED
PRODECOR TESTED

#11 RESISTANCE TO SURFACE WEAR

SOLIDS (150MY): 1550

PRINTS (150MY): 150

#25 RESISTANCE TO IMPACT BY LARGE DIAMETER BALL:

1600MM (62.99")

#29 RESISTANCE TO SCRATCHING: RATING 3

#31 RESISTANCE TO STAINING (METHOD B)

CLEANABILITY SCORE: 16

*MUSTARD SEVERE EFFECT *IODINE MODERATE EFFECT

#33 LIGHT FASTNESS (XENON ARC) (METHOD B)

(5) NO EFFECT (SOLID OR PRINT)

#41 RESISTANCE TO WET HEAT (100° C)

(5) NO VISABLE CHANGE

ASTM E84: CLASS A

REDUCED ENVIRONMENTAL IMPACT

R.E.A.C.H. COMPLIANT

MANUFACTURED WITHOUT PLASTICIZERS OR HEAVY

METALS FIRE CLASSIFICATION EN 13501-1 - CFI - S1



COMPLEMENTARY MATERIALS

[CLICK HERE](#)

