

# PRODUCT FACT SHEET

D	D			ш	C1	ΓΝ		M	
	K	U	U	U			IA	M	_

SSI Prodecor 2D PP Film



## PRODUCT SETUP

Sustainable Cast Polypropylene (PP) film for furniture industry. Applicable as front, backing and drawer film.

Prodecor is PVC free, plasticizer free, and melamine free and and excellently suited for areas with increased moisture exposure.

Depending on the film, ideal for flat lamination, 1D as well as 2D lamination – optionally printed, embossed and lacquered.

## APPLICATION

#### MATERIAL

## Polypropylene

## WIDTH AND THICKNESS

Thickness range: 120-200 µm

Width up to 2,200 mm





COLOR CONSISTENCY

 $\Delta E 0.5-1.0$ 

GLOSS LEVEL 60° MD

Lacquered: 3-6

Non-lacquered: different ranges possible

SURFACE RESISTANCE TO MICRO SCRATCHING (IOS-TM-0002/20 VERS.11)

Martindale tester 902 W: rating 2-3\* \* No visible scratches. Insignificant change of

gloss

SURFACE RESISTANCE
TO COLD LIQUIDS
(IINI FN 42720·2043)

Staining agents	Contact Time	Rating
Water	24h	5
Water	16h	5
Paraffin oil	24h	5
Coffee	1h	5
Ethanol (sol. 48%)	1h	5

## BALL IMPACT RESISTANCE

(DIN EN 13329 & DIN EN 438-2)

Resistance to impact stress with a large ball (diameter of impression >10 mm according to DIN EN 13329): no fissures appeared in the film

These data are only randomly checked and are not equally applicable to all film types. Therefore, no data can be guaranteed.