



COMPLEMENTARY MATERIALS
[CLICK HERE](#)



TAWNY TRAIL

Tawny Trail is an earthy grounded natural coloration which is the perfect design to act as a conscious foundational element. It works as the thread that connects heritage and vintage pieces, dark moody solids and metallics with warm bronze and silver finishes. It is a clean crisp woodgrain design that is accented by the latest modern woodpore texture, contributing to its appealing haptic quality and creating a timeless look. Tawny Trail is featured in SSI's Collection trend and is partnered here with the solid super mattes Ivory Beige, Living Coral and Verde.

Tawny Trail is offered in a furniture like textured finish and is suitable for vertical and horizontal applications. It is easy to clean, doesn't chip, is highly durable and has long term UV Stability.

PENTADECOR® 3D LAMINATE
Color code: EI/6201
Parallel ✓





TAWNY TRAIL

PENTADECOR® 3D LAMINATE

STOCK RANGE ✓ PARALLEL ✓

COLOR CODE: EI/6201 **EMBOSSING:** H08 **TOPCOAT:** MATTE LINE

PERFORMANCE SUMMARY

- BLEACH SOLUTION CLEANABLE
- EXCELLENT SOIL & STAIN RESISTANCE
- NATURAL FLUID BARRIER
- EXCELLENT ABRASION & IMPACT RESISTANCE
- EXCELLENT COLOR STABILITY

ENVIRONMENTAL

- NO ADDED FLAME RETARDANTS
- NO ADDED ANTIMICROBIALS
- DOES NOT CONTAIN FORMALDEHYDE
- FORMULATED WITHOUT PHTHALATES

CLEANING AND MAINTENANCE

- WATER AND MILD LIQUID SOAP CLEANABLE



ITEM SPECIFICATIONS


CONTENT: PVC MOQ : NONE
 SURFACE TEXTURE/EMBOSSING : Modern Woodpore
 SURFACE GLOSS : Level 6 SURFACE FINISH
 LACQUER : Scratch & Stain Resistant Polyurethane
 GAUGE : .014" (350my) WIDTH : 57" (1450mm)
 ROLL SIZE : 250 lm/Roll
 DESIGN REPEAT (RAPPORT) : 1300mm (51/1")
 SUITABLE FOR : Membrane Pressing - Flat Lamination
 - Profile Wrapping - Miter Folding

PERFORMANCE CHARACTERISTICS

3.8 BALL IMPACT NEMA* : >3000MM (118")
 3.9 IMPACT RESISTANCE NEMA* : >1000MM (39") 3.13
 WEAR RESISTANCE NEMA* : 3250 cycles
 3.4 CLEANABILITY & STAIN RESISTANCE NEMA* : 14
 LIGHT FASTNESS ISO 105-BO2 WBS : 6-7
 LIGHT REFLECTIVE VALUE (LRV) : 23.4
 FLUID BARRIER : Inherent Fluid Barrier (Naturally Hydrophobic)
 MEDICAL REAGENTS : Compatible with Common Cleaners, Reagents and Disinfectants used in N.A.
 ASTM E84 : CLASS A
 REDUCED ENVIRONMENTAL IMPACT: Manufactured without Plasticizers, Phthalates, or Heavy Metals

COMPLEMENTARY MATERIALS

[CLICK HERE](#)



Test results may vary by color and design

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be understood as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed.