

# WILLOW GREY SM

WILLOW GREY SM IS A SOFT-TONED GREY COLORATION BASED ON THE FINE, HAIR-LIKE STRAINS ON CATKINS FOUND ON MALE TWIGS OF A WILLOW TREE. THE SOFT GREY SUPER MATTE ALLOWS FOR EASY MATCHING TO MOST ANY SOLID COLOR OR WOODGRAIN LAMINATE DESIGN.

WILLOW GREY'S SUPER MATTE FINISH HAS THE LOOK AND FEEL OF A HIGH QUALITY PAINTED FINISH, BUT WITH SUPERIOR PERFORMANCE. IT IS EASY TO CLEAN, DOESN'T CHIP. IS HIGHLY DURABLE AND HAS LONG TERM UV COLOR STABILITY.

COMPLEMENTARY MATERIALS CLICK HERE

PENTADECOR® 3D LAMINATE COLOR CODE: 75/8101 PARALLEL × =





# WILLOW GREY SM

## PENTADECOR® 3D LAMINATE

STOCK RANGE 🗸 🛛 PARALLEL 🗙 🖨

COLOR CODE: 75/8101 EMBOSSING: A16 ML TOPCOAT: MATTE LINE (ML)

#### PERFORMANCE SUMMARY

- BLEACH SOLUTION CLEANABLE
- EXCELLENT SOIL & STAIN RESISTANCE
- NATURAL FLUID BARRIER
- EXCELLENT ABRASION & IMPACT RESISTANCE
- EXCELLENT COLOR STABILITY

## ENVIRONMENTAL

- NO ADDED FLAME RETARDANTS
- NO ADDED ANTIMICROBIALS
- DOES NOT CONTAIN FORMALDEHYDE
- FORMULATED WITHOUT PHTHALATES

### CLEANING AND MAINTENANCE

WATER AND MILD LIQUID SOAP CLEANABLE

### ITEM SPECIFICATIONS

MOQ : NONE SURFACE TEXTURE/EMBOSSING : SMOOTH SURFACE SURFACE GLOSS : LEVEL 6 SURFACE FINISH LACQUER : SCRATCH & STAIN RESISTANT POLYURETHANE GAUGE : .012" (300MY) WIDTH : 57" (1450MM) ROLL SIZE : 250 LM/ROLL DESIGN REPEAT (RAPPORT) : SOLID COLOR ∞

SUITABLE FOR : MEMBRANE PRESSING - FLAT

LAMINATION - PROFILE WRAPPING - MITER FOLDING

#### PERFORMANCE CHARACTERISTICS

3.8 BALL IMPACT NEMA\* : >3000MM (118") 3.9 IMPACT RESISTANCE NEMA\* : >1000MM (39") 3.13 WEAR RESISTANCE NEMA\* : 3250 CYCLES 3.4 CLEANABILITY & STAIN RESISTANCE NEMA\* : 14 LIGHT FASTNESS ISO 105-BO2 WBS : 6-7 LIGHT REFLECTIVE VALUE (LRV) : 59.85 FLUID BARRIER : INHERENT FLUID BARRIER (NATURALLY HYDROPHOBIC) MEDICAL REAGENTS : COMPATIBLE WITH COMMON CLEANERS, REAGENTS AND DISINFECTANTS USED IN N.A. ASTM E84 : CLASS A

REDUCED ENVIRONMENTAL IMPACT: MANUFACTURED WITHOUT PLASTICIZERS, PHTHALATES, OR HEAVY METALS

COMPLEMENTARY MATERIALS CLICK HERE

\*Test results may vary by color and design\*

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be understood as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industral property rights must be observed.