



## TIMBERLINE RUSTIC OAK

TIMBERLINE RUSTIC OAK REFLECTS THE RUGGED BEAUTY FORGED BY THE PACIFIC NORTHWEST. SUBTLE WEATHERED GRAYS AND MINERAL STREAKS INTERTWINE WITH WARM HONEYED AMBERS AND RICH TAUPE UNDERTONES, EVOKING STORMY SKIES, ROCKY SHORES, AND TIMELESS COASTAL TIMBER. THE PRONOUNCED TACTILE TEXTURE ADDS AUTHENTIC DEPTH AND DIMENSION, DELIVERING BOTH VISUAL DRAMA AND A SATISFYING HAND-FEEL THAT BRINGS THE OUTDOORS IN. THIS BOLD WOODGRAIN DESIGN CAPTURES A DRAMATIC HAND-HEWN CHARACTER WITH DEEP, GRAIN MOVEMENT THAT FLOWS LIKE SHIFTING EARTH AND DRIFTING MIST.

TIMBERLINE RUSTIC OAK IS OFFERED IN A FURNITURE LIKE TEXTURED FINISH AND IS SUITABLE FOR VERTICAL AND HORIZONTAL APPLICATIONS. IT IS EASY TO CLEAN, DOESN'T CHIP, IS HIGHLY DURABLE AND HAS LONG TERM UV STABILITY.

**COMPLEMENTARY MATERIALS**

[CLICK HERE](#)



PRODECOR® 2D PP FILM  
COLOR CODE: SSI/031  
PARALLEL ✓





# TIMBERLINE RUSTIC OAK

## PRODECOR® 2D PP FILM

STOCK RANGE ✓ PARALLEL ✓

COLOR CODE: SSI/031. EMBOSSING: MODERN WOODPORE

### PERFORMANCE SUMMARY

- BLEACH SOLUTION CLEANABLE
- EXCELLENT SOIL & STAIN RESISTANCE
- NATURAL FLUID BARRIER
- EXCELLENT ABRASION & IMPACT RESISTANCE
- EXCELLENT COLOR STABILITY

### ENVIRONMENTAL

- NO ADDED FLAME RETARDANTS
- NO ADDED ANTIMICROBIALS
- DOES NOT CONTAIN FORMALDEHYDE
- FORMULATED WITHOUT PHTHALATES

### CLEANING AND MAINTENANCE

• WATER AND MILD LIQUID SOAP CLEANABLE

### ITEM SPECIFICATIONS

**BRAND NAME:** PRODECOR  
**CONTENT:** POLYPROPOLYENE  
**MOQ:** NONE  
**SURFACE TEXTURE / EMBOSSING:** MODERN WOODPORE  
**SURFACE GLOSS:** 3  
**SURFACE FINISH LACQUER:**  
**SCRATCH & STAIN RESISTANT EXCIMER TOPCOAT**  
**GAUGE:** 150MY (.006") **WIDTH:** 1,300MM (51.18")  
**ROLL SIZE:** 500LM  
**DESIGN REPEAT (RAPPORT):** 1260MM (49.6")  
**SUITABLE FOR:** FLAT LAMINATION, PROFILE WRAPPING

### PERFORMANCE CHARACTERISTICS

**TESTING DONE IN ACCORDANCE TO:** ISO 4586-1 2018-07  
 150MY SOLID AND 150MY PRINTED EXCIMER TOP COATED  
 PRODECOR TESTED

**#11 RESISTANCE TO SURFACE WEAR**  
**SOLIDS (150MY):** 1550  
**PRINTS (150MY):** 150

**#25 RESISTANCE TO IMPACT BY LARGE DIAMETER BALL:**  
 1600MM (62.99")

**#29 RESISTANCE TO SCRATCHING:** RATING 3  
**#31 RESISTANCE TO STAINING (METHOD B)**  
**CLEANABILITY SCORE:** 16

**\*MUSTARD SEVERE EFFECT \*IODINE MODERATE EFFECT**  
**#33 LIGHT FASTNESS (XENON ARC) (METHOD B)**  
 (5) NO EFFECT (SOLID OR PRINT)

**#41 RESISTANCE TO WET HEAT (100° C)**  
 (5) NO VISABLE CHANGE

**REDUCED ENVIRONMENTAL IMPACT**  
**R.E.A.C.H. COMPLIANT**  
**MANUFACTURED WITHOUT PLASTICIZERS OR HEAVY METALS**  
**FIRE CLASSIFICATION** EN 13501-1 - CFI - S1



### COMPLEMENTARY MATERIALS

[CLICK HERE](#)

